




Ecoline

8 792 055 119
11 × 2,1 W, 1414 lm, 4000 K neutral white, DALI,
narrow beam 6° ,



Customized solutions and modifications are possible: Special RAL,
DB or NCS colours as polyester powder coat, luminaires in
2700 K and other colour temperatures and versions for high
ambient temperature.

Specification text

housing made of extruded aluminum and corrosion-resistant
die-cast aluminum AlSi12, polyester powder coated by
high-quality and UV-stabilized coating process, Colour: silver grey
 , all exterior parts are stainless steel, UV stabilised,
impact-resistant polycarbonate cover with partial frosting for
uniform light diffraction, silicon gasket, closure with 2 stainless
steel screws, mounting flanges: 2 drilled holes Ø 6.5 mm,
spacing L2, tilt range: 220°, cable gland: M20,
connecting terminal: 5 pole, highly efficient optics made of
transparent thermoplastic for precise lighting tasks , integral driver
(DALI), CRI > 80, max 2 SDCM,
service life L90/B10 > 50.000 h, Beam angle (FWHM): 6° ,
luminous flux: 1414 lm, wattage: 23 W, delivered lumens
61 lm/W, protection type IP65, protection class I,
impact resistance IK10, windage area 0,1 m²,
dimensions (L×H×W): 662 × 57 × 54 mm, weight 2.3 kg

The modular luminaire design makes the replacement of
components possible. The product meets the demands of the
applicable EU guidelines and product safety regulations and
bears the CE and ENEC marks.



Specification

Wattage	23 W	Beam angle (FWHM)	6°
Delivered lumens	61 lm/W	Housing colour	silver grey
Light source	LED 4000 K	Power supply cable	Ø 6 – 10 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	L90/B10 > 50.000 h	Impact resistance	IK10
Control gear	DALI	Windage area	0,1m²
Input voltage AC	220 – 240 V	Dimensions	662 × 57 × 54 mm
Input voltage DC	200 – 265 V	Weight	2,30 kg
Voltage protection	1 kV L/N 2 kV L/PE	Max. ambient temperature ta	40°
Luminaires per B16A / C16A	28 / 46		