






### Ecovision Mini

8 706 146 209  
6 × 2,5 W, 1175 lm, 3000 K warm white, 1-10V,  
wall washer 15° / 103°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

### Specification text

housing made corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, UV stabilised, impact-resistant polycarbonate cover, silicon gasket, with 4 stainless steel screws, wall arm: 2 drilled holes Ø 6,5 mm, spacing 282 mm, tilt range: 310°, cable gland: PG11, connecting terminal: 5 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (1-10V), CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 15° / 103°, luminous flux: 1175 lm, wattage: 15 W, delivered lumens 78 lm/W, protection type IP65, protection class I, impact resistance IK10, windage area 0,04 m², dimensions (L×H×W): 328 × 47 × 135 mm, weight 3.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK10

### Specification

|                       |                    |                             |                   |
|-----------------------|--------------------|-----------------------------|-------------------|
| Wattage               | 15 W               | Beam angle (FWHM)           | 15° / 103°        |
| Delivered lumens      | 78 lm/W            | Housing colour              | black RAL 7021    |
| Light source          | LED 3000 K         | Power supply cable          | Ø 7 – 9 mm        |
| Color Rendering Index | CRI > 80           | Protection type             | IP65              |
| Colour tolerance      | max 2 SDCM         | Protection class            | I                 |
| Lifetime ta 25° C     | L90/B10 > 50.000 h | Impact resistance           | IK10              |
| Control gear          | 1-10V              | Windage area                | 0,04m²            |
|                       |                    | Dimensions                  | 328 × 47 × 135 mm |
|                       |                    | Weight                      | 3,10 kg           |
|                       |                    | Max. ambient temperature ta | 35°               |