






Monocube 4

8 264 256 129
16 × 2,3 W, 2762 lm, 3000 K warm white, DALI,
linear, vertical 54° / 7°



Customized solutions and modifications are possible: Special RAL,
DB or NCS colours as polyester powder coat, luminaires in
2700 K and other colour temperatures and versions for high
ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12,
polyester powder coated by high-quality and UV-stabilized
coating process, Colour: silver grey, all exterior parts are
stainless steel, tempered safety glass, anti-reflective coating from
1 side, dark screenprint, silicon gasket, closure with 4 stainless
steel screws, for installation on poles Ø 60 - 100 mm, tiltable
base made of powder coated aluminum, 2 drilled holes Ø 9 mm,
spacing 95 mm, 1 centre hole Ø 13.5 mm, tilt range:
90°, 360° adjustable, cable gland: M20, connecting terminal:
5 pole, precise PMMA optics, integral driver (DALI), CRI > 80,
max 2 SDCM, service life L90/B10 > 50.000 h,
Beam angle (FWHM): 54° / 7°, luminous flux: 2762 lm,
wattage: 37 W, delivered lumens 75 lm/W, protection type
IP65, protection class I, impact resistance IK08, windage area
0,022 m², dimensions (L×H×W): 152 × 120 × 152 mm, weight
2.4 kg

The modular luminaire design makes the replacement of
components possible. The product meets the demands of the
applicable EU guidelines and product safety regulations and
bears the CE mark.

IP65 IK08

Specification

Wattage	37 W	Beam angle (FWHM)	54° / 7°
Delivered lumens	75 lm/W	Housing colour	silver grey
Light source	LED 3000 K	Power supply cable	Ø 6 – 13 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	L90/B10 > 50.000 h	Impact resistance	IK08
Control gear	DALI	Windage area	0,022m²
Input voltage AC	220 – 240 V	Dimensions	152 × 120 × 152 mm
Input voltage DC	220 – 240 V	Weight	2,40 kg
Voltage protection	4 kV L/N 2 kV L/PE	Max. ambient temperature ta	35°
Luminaires per B16A / C16A	23 / 39		