







**MonoFlood 4**

8 204 066 079  
13 × 7,5 W, 4720 lm, 3000 K warm white,  
linear, rotatable 9° / 40°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

**Specification text**

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 4 stainless steel screws, mounting bracket: 2 drilled holes Ø 7 mm, spacing 40 - 60 mm, 1 centre hole Ø 21 mm, tilt range: 180°, cable gland: M20, connecting terminal: 3 pole, precise PMMA optics, integral driver (AC/DC), CRI > 80, max 3 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 9° / 40°, luminous flux: 4720 lm, wattage: 98 W, delivered lumens 48 lm/W, protection type IP67, protection class I, impact resistance IK10, windage area 0,046 m², dimensions (L×H×W): 250 × 176 × 250 mm, weight 7 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



**Specification**

|                       |                       |                             |                    |
|-----------------------|-----------------------|-----------------------------|--------------------|
| Wattage               | 98 W                  | Beam angle (FWHM)           | 9° / 40°           |
| Delivered lumens      | 48 lm/W               | Housing colour              | white RAL 9002     |
| Light source          | LED 3000 K            | Power supply cable          | Ø 6 – 13 mm        |
| Color Rendering Index | CRI > 80              | Protection type             | IP67               |
| Colour tolerance      | max 3 SDCM            | Protection class            | I                  |
| Lifetime ta 25° C     | L90/B10 > 50.000 h    | Impact resistance           | IK10               |
| Control gear          | on / off              | Windage area                | 0,046m²            |
| Input voltage AC      | 100 – 280 V           | Dimensions                  | 250 × 176 × 250 mm |
| Input voltage DC      | 140 – 380 V           | Weight                      | 7,00 kg            |
| Voltage protection    | 4 kV L/N   10 kV L/PE | Max. ambient temperature ta | 35°                |