



8 250 066 149



## Specification

housing made of corrosion-resistant die-cast aluminum ALSi12,  
polyester powder coated by high-quality and UV-stabilized  
coating process, Colour: white RAL 9002, all exterior parts are  
stainless steel, tempered high efficiency safety glass, anti-reflective  
coating from 1 side, dark screenprint, silicon gasket, closure with  
4 stainless steel screws, mounting bracket: 2 drilled holes Ø 7  
mm, spacing 40 - 50 mm, 1 centre hole Ø 21 mm, tilt range:  
180°, cable gland: M20, connecting terminal: 5 pole, highly  
efficient metallized PC reflector, integral driver (DALI), CRI > 80,  
3 SCDM, service life L80/B20 > 50.000 h, luminous flux:  
5618 lm, wattage: 46 W, delivered lumens 122 lm/W,  
protection type IP67, protection class I, impact resistance IK08,  
windage area 0,063 m², dimensions (L×H×W):  
362 × 67 × 308 mm, weight 4.5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP 67 IK 08

Wattage	46 W	Housing colour	white RAL 9002
Delivered lumens	1 22 lm/W	Power supply cable	Ø 5 – 14 mm
Light source	LED 3000 K	Protection type	IP67
Color Rendering Index	CRI > 80	Protection class	I
Colour tolerance	3 SCDM	Impact resistance	IK08
Lifetime ta 25° C	L80/B20 > 50.000 h	Windage area	0,063m²
Control gear	DALI	Dimensions	362 × 67 × 308 mm
Input voltage AC	220 – 240 V	Weight	4,50 kg
Voltage protection	3 kV L/N   4 kV L/PE	Max. ambient temperature ta	35°
Luminaires per B16A / C16A	15 / 25		