





## **Monospace**

8 250 356 149  $4 \times 11,5$  W, 5618 lm, 3000 K warm white, DALI,







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## **Specification text**

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 4 stainless steel screws, with pole top fitter for 1 luminaire for poles Ø 60/76 mm, 3 M8 grub screws, tilt range: 7°, cable gland: M20, with 8 m cable Ho5RN-F5G1, connecting terminal: 5 pole, highly efficient metallized PC reflector, integral driver (DALI), CRI > 80, 3 SCDM, service life L80/B20 > 50.000 h, luminous flux: 5618 lm, wattage: 46 W, delivered lumens 122 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,063 m², dimensions (L×H×W): 362 × 67 × 308 mm, weight 5.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





IP67 IK08

## Specification

Wattage 46 W Housing colour silver grey Delivered lumens 122 lm/W Power supply cable  $\emptyset$  5 - 14 mm Light source LED 3000 K Protection type IP67 Protection class Color Rendering Index CRI > 80 Ι Colour tolerance 3 SCDM Impact resistance IKo8 Lifetime ta 25° C L80/B20 > 50.000 h Windage area  $0,063m^{2}$ Control gear DALI Dimensions 362 × 67 × 308 mm 5,10 kg Input voltage AC 220 - 240 V Weight 3 kV L/N | 4 kV L/PE Max. ambient temperature ta 35° Voltage protection Luminaires per B16A / C16A 15 / 25