




## Monospace

 $8\ 250\ 465\ 109$   $_2\times 55\ W,\ 8339\ lm,\ 4000\ K$  neutral white, DALI,







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered high efflency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 4 stainless steel screws, with pole top fitter for 2 luminaires for poles Ø 60/76 mm, 3 M8 grub screws, tilt range: 7°, cable gland: M20, with 2x 8 m cable Ho5RN-F5G1, connecting terminal: 5 pole, micro-prism optic directs light under defined angles and achieves, together with shielded LEDs, perfect glare control , integral driver (DALI), CRI > 80, 3 SCDM, service life L80/B20 > 50.000 h,

Beam angle (FWHM): 71 ° / 139°, luminous flux: 8339 lm, wattage: 110 W, delivered lumens 76 lm/W, protection type IP67, protection class I, impact resistance IKo8, windage area 0,063 m², dimensions (L×H×W): 924 × 67 × 308 mm, weight 9.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





IP67 IK08

## Specification

Wattage 110 W

Delivered lumens 76 lm/W

Light source LED 4000 K

Color Rendering Index CRI > 80

Colour tolerance 3 SCDM

Lifetime ta 25° C L80/B20 > 50.000 h

Control gear DALI

Beam angle (FWHM) 71°/139° Housing colour white RAL 9002 Power supply cable  $\emptyset$  5 – 14 mm Protection type IP67 Protection class Impact resistance IKo8 Windage area  $0.063 \,\mathrm{m}^2$ Dimensions 924 × 67 × 308 mm Weight 9,80 kg

Max. ambient temperature ta 35°