







8 252 055 049



Specification

housing made of corrosion-resistant die-cast aluminum ALSi12,
polyester powder coated by high-quality and UV-stabilized
coating process, Colour: silver grey , all exterior parts are
stainless steel, tempered high efficiency safety glass, anti-reflective
coating from 1 side, dark screenprint, silicon gasket, closure with
4 stainless steel screws, mounting bracket: 2 drilled holes Ø 7
mm, spacing 40 - 50 mm, 1 centre hole Ø 21 mm, tilt range:
180°, cable gland: M20, connecting terminal: 3 pole, highly
efficient metallized PC reflector, integral control gear, CRI > 80,
3 SCDM, service life L80/B20 > 50.000 h, luminous flux:
5899 lm, wattage: 46 W, delivered lumens 128 lm/W,
protection type IP67, protection class II, impact resistance IK08,
windage area 0,063 m², dimensions (L×H×W):
362 × 67 × 308 mm, weight 4.5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP 67 IK08

Wattage	46 W	Housing colour	silver grey
Delivered lumens	1 28 lm/W	Power supply cable	Ø 5 – 14 mm
Light source	LED 4000 K	Protection type	IP67
Color Rendering Index	CRI > 80	Protection class	II
Colour tolerance	3 SCDM	Impact resistance	IK08
Lifetime ta 25° C	L80/B20 > 50.000 h	Windage area	0,063m²
Control gear	on / off	Dimensions	362 × 67 × 308 mm
Input voltage AC	220 – 240 V	Weight	4,50 kg
Input voltage DC	220 – 240 V	Max. ambient temperature ta	35°
Voltage protection	4 kV L/N 2 kV L/PE		
Luminaires per B16A / C16A	27 / 46		