







Monospot Gobo

8 905 056 149

55 W, 1445 lm, 3000 K warm white, DALI,
85 mm focal length 22°



Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 3 stainless steel screws, mounting bracket powder coated aluminum with tilt scale: 2 drilled holes Ø 7 mm, spacing 40 - 60 mm, 1 centre hole Ø 21 mm, tilt range: 180°, cable gland: M20, connecting terminal: 5 pole, focusable projection lens for precise light control and sharp-edged image projections, integral driver (DALI), CRI > 80, Beam angle (FWHM): 22°, luminous flux: 1445 lm, wattage: 55 W, delivered lumens 26 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,076 m², dimensions: Ø 215 mm, width 390 mm, weight 8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

Specification

Wattage	55 W
Delivered lumens	26 lm/W
Light source	LED 3000 K
Color Rendering Index	CRI > 80
Control gear	DALI
Input voltage AC	220 – 240 V
Input voltage DC	220 – 240 V
Voltage protection	2 kV L/N 4 kV L/PE
Luminaires per B16A / C16A	23 / 39

Beam angle (FWHM)	22°
Housing colour	silver grey
Power supply cable	Ø 6 – 13 mm
Protection type	IP65
Protection class	I
Impact resistance	IK08
Windage area	0,076m²
Dimensions	Ø 215 mm, width 390 mm
Weight	8,00 kg
Max. ambient temperature ta	35°