







## Monospot S2

8 992 055 049

4 × 2,5 W, 536 lm, 4000 K neutral white,  
medium wide beam 27°



## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 2 stainless steel screws, mounting bracket: 1 elongated hole Ø 7 mm, spacing 18 mm, 1 centre hole Ø 8.5 mm, tilt range: 180°, cable gland: M16, connecting terminal: 3 pole, precise PMMA optics, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 27°, luminous flux: 536 lm, wattage: 10 W, delivered lumens 54 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,012 m², dimensions: Ø 123 mm, width 87 mm, weight 1.2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP 67 IK 08

Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification

|                            |                      |                             |                       |
|----------------------------|----------------------|-----------------------------|-----------------------|
| Wattage                    | 10 W                 | Beam angle (FWHM)           | 27°                   |
| Delivered lumens           | 54 lm/W              | Housing colour              | silver grey           |
| Light source               | LED 4000 K           | Power supply cable          | Ø 5 – 9 mm            |
| Color Rendering Index      | CRI > 80             | Protection type             | IP67                  |
| Colour tolerance           | max 2 SDCM           | Protection class            | I                     |
| Lifetime ta 25° C          | L90/B10 > 50.000 h   | Impact resistance           | IK08                  |
| Control gear               | on / off             | Windage area                | 0,012m²               |
| Input voltage AC           | 220 – 240 V          | Dimensions                  | Ø 123 mm, width 87 mm |
| Input voltage DC           | 220 – 240 V          | Weight                      | 1,20 kg               |
| Voltage protection         | 2 kV L/N   4 kV L/PE | Max. ambient temperature ta | 45°                   |
| Luminaires per B16A / C16A | 50 / 50              |                             |                       |