







Monospot 4

8 904 069 019
49 W, 1 442 lm, RGBW (3000 K) DMX,
narrow beam 9°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 3 stainless steel screws, bracket: 2 long holes Ø 7 mm, spacing 40-60 mm, 1 centre hole Ø 21 mm, tilt range: 180°, cable gland: M20, connecting terminal: 6 pole, highly efficient faceted rotationally symmetrical reflector, integral driver (AC/DC), Beam angle (FWHM): 9°, luminous flux: 1 442 lm, wattage: 49 W, delivered lumens 29 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,075 m², dimensions: Ø 210 mm, width 240 mm, weight 4.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.

  IP 67 IK08

Specification

Wattage	49 W	Beam angle (FWHM)	9°
Delivered lumens	29 lm/W	Housing colour	white RAL 9002
Light source	LED RGBW (3000 K)	Power supply cable	Ø 6 – 13 mm
Control gear	DMX	Protection type	IP67
Input voltage AC	120 – 277 V	Protection class	I
Input voltage DC	120 – 250 V	Impact resistance	IK08
Luminaires per B16A / C16A	22 / 22	Windage area	0,075m²
		Dimensions	Ø 210 mm, width 240 mm
		Weight	4,80 kg
		Max. ambient temperature ta	35°