






Monospot 3

8 907 267 099  
36 W, 2732 lm, 2700 K warm white,  
asymmetrical 18°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 3 stainless steel screws, for installation on poles Ø 60 - 100 mm, tiltable base made of powder coated aluminum, 2 drilled holes Ø 9 mm, spacing 95 mm, 1 centre hole Ø 13.5 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 3 pole, high efficiency asymmetrical aluminum reflector, integral driver (AC/DC), CRI > 80, max 2 SCDM, service life L90/B10 > 50.000 h, luminous flux: 2732 lm, wattage: 36 W, delivered lumens 77 lm/W, protection type IP67, protection class II, impact resistance IK08, windage area 0,049 m², dimensions: Ø 175 mm, width 200 mm, weight 3.5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



Specification

|                            |                      |                             |                        |
|----------------------------|----------------------|-----------------------------|------------------------|
| Wattage                    | 36 W                 | Housing colour              | white RAL 9002         |
| Delivered lumens           | 77 lm/W              | Power supply cable          | Ø 6 – 13 mm            |
| Light source               | LED 2700 K           | Protection type             | IP67                   |
| Color Rendering Index      | CRI > 80             | Protection class            | II                     |
| Colour tolerance           | max 2 SCDM           | Impact resistance           | IK08                   |
| Lifetime ta 25° C          | L90/B10 > 50.000 h   | Windage area                | 0,049m²                |
| Control gear               | on / off             | Dimensions                  | Ø 175 mm, width 200 mm |
| Input voltage AC           | 110 – 240 V          | Weight                      | 3,50 kg                |
| Input voltage DC           | 190 – 250 V          | Max. ambient temperature ta | 35°                    |
| Voltage protection         | 4 kV L/N   5 kV L/PE |                             |                        |
| Luminaires per B16A / C16A | 30 / 51              |                             |                        |