






Monospot 4

8 908 266 089
68 W, 7210 lm, 3000 K warm white,
Street Optic 92° / 143°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 3 stainless steel screws, for installation on poles Ø 60 - 100 mm, tiltable base made of powder coated aluminum, 2 drilled holes Ø 9 mm, spacing 95 mm, 1 centre hole Ø 13.5 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 3 pole, lens for batwing light distribution made of highly efficient optical silicon, integral driver (AC/DC), CRI > 85, max 3 SDCM, service life L80/B20 > 50.000 h, Beam angle (FWHM): 92° / 143°, luminous flux: 7210 lm, wattage: 68 W, delivered lumens 107 lm/W, protection type IP67, protection class II, impact resistance IK08, windage area 0,075 m², dimensions: Ø 215 mm, width 240 mm, weight 5.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP67 IK08

Specification

Wattage	68 W
Delivered lumens	107 lm/W
Light source	LED 3000 K
Color Rendering Index	CRI > 85
Colour tolerance	max 3 SDCM
Lifetime ta 25° C	L80/B20 > 50.000 h
Control gear	on / off
Input voltage AC	220 – 240 V
Input voltage DC	195 – 255 V
Voltage protection	2 kV L/N 4 kV L/PE
Luminaires per B16A / C16A	10 / 16

Beam angle (FWHM)	92° / 143°
Housing colour	white RAL 9002
Protection type	IP67
Protection class	II
Impact resistance	IK08
Windage area	0,075m²
Dimensions	Ø 215 mm, width 240 mm
Weight	5,10 kg
Max. ambient temperature ta	35°