






8 308 145 089



Specification text

cable entry for recessed cable Ø 7-10 mm , connecting terminal:
3 pole, highly efficient optic made of high gloss thermoplastic for
precise light control , integral driver (AC/DC), CRI > 80,
max 3 SDCM, service life L90/B10 > 50.000 h, luminous flux:
248 lm, wattage: 5 W, delivered lumens 46 lm/W,
protection type IP65, protection class I, impact resistance IK07,
windage area 0,005 m², dimensions (L×H×W):
61 × 67 × 81 mm, weight 0.47 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK07

Specification

Wattage	5 W	Housing colour	black RAL 7021
Delivered lumens	46 lm/W	Protection type	IP65
Light source	LED 4000 K	Protection class	I
Color Rendering Index	CRI > 80	Impact resistance	IK07
Colour tolerance	max 3 SDCM	Windage area	0,005m ²
Lifetime ta 25° C	L90/B10 > 50.000 h	Dimensions	61 × 67 × 81 mm
Control gear	on / off	Weight	0,47 kg
Input voltage AC	100 – 240 V	Max. ambient temperature ta	45°
Voltage protection	1 kV L/N 1 kV L/PE		
Luminaires per B16A / C16A	154 / 154		